



## AGS COMMERCIAL LOUVRE ADAPTOR

The AGS Commercial Louvre Adaptor gives you the flexibility you need to create a high-performance louvre window with a clean architectural finish.

Simply pair the AGS Commercial Louvre Adaptor with any AGS Commercial framing system to convert it into a louvre window with ease.

Once installed, framing systems are compatible with both our manual and automatic louvre gallery variants, allowing you to choose between multiple blade, handle style and screening options to suit your requirements.

### FEATURES AND BENEFITS

- An extremely simple system consisting of two extrusions
- Extrusions can be fitted to any of Capral's commercial framing systems, converting the configuration to a louvre window
- When paired with the AGS 419 Flushline 150mm Single Glazed range, the result is a very clean architectural style window, which provides clearance to fully open the 152mm louvre blades behind the fully integrated fly/security screen
- Adaptors are compatible with the full range of Ventus Louvre Galleries

### MAXIMUM PERFORMANCE

Serviceability Pressure*	
Ultimate Pressure	8000Pa
Water Penetration	250Pa

\*Refer to relevant commercial framing system manual for serviceability pressure performance

### FRAME DIMENSIONS

	Depth	Height
SG Flushline	150mm	50mm

\*Can also be using with any commercial framing system

### MAXIMUM RECOMMENDED SIZE

Height	2100mm
Width	900mm

### LOUVRE BLADE DETAILS

6mm Glass	102mm or 152mm
Elliptical Aluminium	102mm or 152mm
Flat Aluminium	152mm

### WINDOW ENERGY RATINGS

Window ID	Glazing	Uw	SHGC	T <sub>w</sub>	Air Inf
CAP-527-01	6Clr	6.20	0.51	0.53	
CAP-527-02	6ET	4.90	0.43	0.49	
CAP-527-03	6ETGy	5.00	0.30	0.24	
CAP-527-04	6Gy	6.20	0.36	0.25	
CAP-527-05	6LgtGy	6.20	0.41	0.37	



View full list of Residential and Commercial WERs rating at [capral.com.au](http://capral.com.au)