



ags<sup>™</sup>

COMMERCIAL

325 NARROWLINE  
DOUBLE GLAZED (76MM)

CAPRAL  
ALUMINIUM



## AGS 325 NARROWLINE DOUBLE GLAZED (76mm)

The AGS 325 Narrowline double glazed framing system provides a crisp, narrow Commercial appearance in a smaller 76mm x 35mm frame.

Its slimline frame depth and ability to accommodate a captive glazing wedge makes it an economical option for architectural housing, shop front applications of modest dimensions or internal partitioning applications.

### FEATURES AND BENEFITS

- 76mm x 35mm centre glazed framing system
- Suits light-commercial, internal fit-out or architectural applications
- Supports double glazing up to 29mm
- Economical, light weight design
- Captive glazing wedge options for easier on-site glazing
- Sub-frame options
- Compatible door and window suites available
- Dedicated reveal leg frames
- Internal and externally beaded options
- Dedicated corner posts



Capral's AGS range is extruded in Australia using LocAl® Green primary aluminium.

- Significantly lower carbon emissions than global averages for primary aluminium
- 8kg CO<sub>2</sub>e/kg Al\*
- ASI Certified Smelter



\* Capral utilises a Mass Balance System in line with ISO 20095:2020 Chain of Custody to manage its LocAl Products. CO<sub>2</sub>e emissions stated are ex smelter based on kilograms emitted per kilogram of aluminium produced – Aluminium Smelting and Casting, International Aluminum Institute (IAI)



1800 ALUMINIUM (258 646)  
capral.com.au  
Capral Limited ABN 78 004 213 692  
February 2025

### MAXIMUM PERFORMANCE

Serviceability Pressure	2500Pa
Ultimate Pressure	4100Pa
Water Penetration	600Pa

### FRAME DIMENSIONS

Depth	76mm
Height	35mm

### MAXIMUM RECOMMENDED SIZE

Height	3000mm
Width	2200mm

### GLAZING CAPACITY

Double Glazed	18-29mm
---------------	---------

### ACOUSTIC RATING

Acoustics (Max)	39(-1,-3)
-----------------	-----------

### WINDOW ENERGY RATINGS

Window ID	Glazing	Uw	SHGC	T <sub>w</sub>	Air Inf
CAP-123-02	6Clr/12Ar/6Clr	3.1	0.66	0.72	0.02
CAP-123-04	6ET/12Ar/6Clr	2.4	0.58	0.67	0.02
CAP-123-12	AGG IP Clr 6/12Ar/6	2.2	0.52	0.73	0.02
CAP-123-13	AGG IP Clr 5/12Ar/5	2.2	0.52	0.73	0.02
CAP-123-16	AGG PRIME Clr 6/12/6	2.4	0.50	0.62	0.02
CAP-123-18	AGG PRIME Gy 4/12/4	2.4	0.45	0.40	0.02
CAP-123-19	AGG PRIME Gy 6/12/6	2.4	0.37	0.31	0.02
CAP-123-20	AGG PRIME Clr lam 4/12/6.38	2.4	0.51	0.63	0.02
CAP-123-23	AGG PRIME WTrans lam 6/12/6.38	2.4	0.48	0.47	0.02
CAP-123-26	AGG PLUS Clr 6/12/6	2.2	0.54	0.73	0.02
CAP-123-29	AGG PLUS Gy 6/12/6	2.2	0.33	0.36	0.02
CAP-123-31	AGG PLUS Clr lam 6.38/12/6	2.2	0.53	0.73	0.02
CAP-123-37	AGG MAX Clr lam 6/12/6.38	2.1	0.26	0.60	0.02

View full list of Residential and Commercial WERS rating at [capral.com.au](http://capral.com.au)