



ags<sup>TM</sup>

COMMERCIAL  
SLIDING WINDOW

CAPRAL  
ALUMINIUM



## AGS SLIDING WINDOW

The 380 & 480 Sliding Windows incorporate the features and flexibility of a residential window system into the commercial grade AGS 300/325 or 400/425 Narrowline framing systems. Particularly suited to architectural applications where a more substantial, commercial appearance is desired.

The AGS 380 & 480 Sliding Windows deliver a neat and streamlined appearance with their squared mullions and glazing beads. With the use of adaptors, the sashes for both 380 & 480 sliding windows can be double glazed to offer an enhanced level of thermal comfort and performance.

### FEATURES AND BENEFITS

- 76mm or 101.6mm Narrowline outer frames for residential, commercial and architectural applications
- Single and double glazed sash options
- 480 Slider-over-slider functionality
- Integrated head and sill design for neat, clean appearance
- Adjustable rollers and height adjustable lockable latching option
- Integrated insect and security screening options.
- Compatible with AGS 300/325 & 400/425 Narrowline suites.
- Residential perimeter frame available (Urban 280)
- Lockable hardware options.



Capral's AGS range is extruded in Australia using LocAl® Green primary aluminium.

- 50% lower-carbon emissions than global averages for primary aluminium
- 8kg CO<sub>2</sub>e/kg Al
- ASI Certified Smelter



1800 ALUMINIUM (258 646)  
capral.com.au  
Capral Limited ABN 78 004 213 692  
April 2023

### MAXIMUM PERFORMANCE

	380	480
SLS	4500Pa	4500Pa
ULS	10600Pa	11200Pa
Water	300Pa	600Pa

### FRAME DIMENSIONS

380	76mm x 35mm
480	101.6mm x 44mm

### MAXIMUM RECOMMENDED SIZE

Height	1500mm
Width	1200mm
Weight	42kg

### GLAZING CAPACITY

Single Glazed	3-6mm
Double Glazed	10, 16-18mm

### MAXIMUM ACOUSTIC RATING

Acoustics	33 (0;-2)
-----------	-----------

### WINDOW ENERGY RATINGS

Window ID	Glazing	Uw	SHGC	Tww	Air Inf
<b>380</b>					
CAP-543-001	6.38CPGy	4.8	0.42	0.32	0.75
CAP-543-005	6ET	4.8	0.58	0.66	0.75
CAP-543-006	6Clr	6.4	0.69	0.72	0.75
CAP-544-004	4Clr/10/4Clr	4.7	0.57	0.58	0.33
CAP-544-005	4Clr/10Ar/4Clr	4.5	0.57	0.58	0.33
CAP-544-006	4ET/10Ar/4Clr	3.9	0.48	0.54	0.33
<b>480</b>					
CAP-027-001	4Clr/10/4Clr	4.8	0.56	0.58	0.61
CAP-027-003	4Gy/10/4Clr	4.8	0.42	0.36	0.61
CAP-028-001	4Clr	6.9	0.69	0.71	0.61
CAP-028-002	6SpGy	6.9	0.30	0.07	0.61
CAP-028-003	6.38DLam	6.8	0.66	0.70	0.61

View full list of Residential and Commercial WERs rating at [capral.com.au](http://capral.com.au)