



agsTM

COMMERCIAL

400 NARROWLINE
SINGLE GLAZED (101.6MM)

CAPRAL
ALUMINIUM



AGS 400 NARROWLINE SINGLE GLAZED (101.6mm)

The AGS 400 Narrowline framing system has set the standard for centre glazed framing for over two decades. With an aesthetically balanced look and the option of beveled or square finishes, the AGS 400 Narrowline is the most versatile and adaptable framing system in the range.

With a multitude of compatible window and door suites, the AGS 400 Narrowline offers enormous design flexibility making this product ideal for commercial or residential projects that require a bold modern look and high levels of structural performance.

FEATURES AND BENEFITS

- 101.6mm x 44mm centre glazed framing system
- Supports single glazing
- Captive glazing wedge options for easier on-site glazing
- Flexible design with wide range of mullion and transom options
- Sub-frame options
- Compatible door and window suites available
- Internal and externally beaded options
- Dedicated corner posts
- Tested for BAL 40 compliance

MAXIMUM PERFORMANCE

Serviceability Pressure	5200Pa
Ultimate Pressure	10300Pa
Water Penetration	1500Pa

FRAME DIMENSIONS

	Depth	Height
Option 1	101.6mm	44mm
Option 2	101.6mm	28mm

MAXIMUM RECOMMENDED SIZE

Height	4000mm
Width	2400mm

GLAZING CAPACITY

Single Glazed	4-10mm
---------------	--------

GLAZING CAPACITY

Acoustics (Max)	37 (0,-3)
-----------------	-----------

WINDOW ENERGY RATINGS

Window ID	Glazing	Uw	SHGC	Tw	Air Inf
CAP-062-09	6EcAd	4.3	0.57	0.60	0.04
CAP-062-21	10.38DLam	5.9	0.70	0.79	0.04
CAP-062-24	10.38CPClr	4.1	0.58	0.72	0.04
CAP-062-28	10.38SnClr	4.5	0.50	0.60	0.04
CAP-062-29	8.76ESITOGy	4.1	0.31	0.31	0.04
CAP-062-31	6SnClr	4.6	0.54	0.61	0.04
CAP-062-35	6TS21Gy	5.2	0.26	0.09	0.04
CAP-062-40	6SolEGy	4.2	0.33	0.27	0.04
CAP-062-41	6ET	4.1	0.64	0.74	0.04
CAP-062-43	10.38VTlam	5.9	0.60	0.60	0.04
CAP-062-44	6SolT	4.2	0.49	0.57	0.04
CAP-062-47	6ETGn	4.2	0.45	0.64	0.04
CAP-062-50	6EVGy	4.3	0.38	0.29	0.04

View full list of Residential and Commercial WERS rating at capral.com.au



Capral's AGS range is extruded in Australia using LocAl® Green primary aluminium.

- 50% lower-carbon emissions than global averages for primary aluminium
- 8kg CO₂e/kg Al
- ASI Certified Smelter



1800 ALUMINIUM (258 646)
capral.com.au
 Capral Limited ABN 78 004 213 692
 January 2022