



agsTM

COMMERCIAL
659 FLUSHLINE
WIDE POCKET (150MM)

CAPRAL
ALUMINIUM



AGS 659 FLUSHLINE WIDE POCKET (150mm)

The AGS 659 150mm wide pocket commercial Flushline framing system has been developed to accommodate both internal and external glazing techniques. Its front glazed arrangement has been designed to maximise internal areas whilst achieving a clean and modern external appearance.

The AGS 659 Flushline system accepts a variety of glass thicknesses, incorporates optional structurally glazed mullion profiles and offers a number of operable door and window options.

FEATURES AND BENEFITS

- 150x55mm double glazed frame options
- Forward positioned glazing pocket for flush external finish or reverse installation possible for expressed mullions
- Captive glazing wedge options for easier on-site glazing
- Structurally glazed mullion and or transom options
- Compatible door and window suites available
- Supports various glass thicknesses with the use of an adaptor
- Sub frame including spandral sub frame available
- Internal and externally beaded options



Capral's AGS range is extruded in Australia using LocAl® Green primary aluminium.

- 50% lower-carbon emissions than global averages for primary aluminium
- 8kg CO₂e/kg Al
- ASI Certified Smelter



CAPRAL
ALUMINIUM

1800 ALUMINIUM (258 646)
capral.com.au
Capral Limited ABN 78 004 213 692
October 20, 2022 4:09 pm

MAXIMUM PERFORMANCE

Serviceability Pressure	4500Pa
Ultimate Pressure	11000Pa
Water Penetration	1200Pa

FRAME DIMENSIONS

Depth	150mm
Height	55mm

MAXIMUM RECOMMENDED SIZE

Height	5000mm
Width	2400mm

GLAZING CAPACITY

Single Glazed (Adaptor)	5-12mm
Double Glazed	34-41mm

ACOUSTICS

Acoustics (Max)	42 (-2,-5*)
-----------------	-------------

*Based on acoustic opinion

WINDOW ENERGY RATINGS

Window ID	Glazing	Uw	SHGC	Tw	Air Inf
CAP-059-114	6SolTGy/12Ar/6Clr	2.8	0.25	0.24	0.09
CAP-063-114	AGG IP Ctr 6/12Ar/6	2.4	0.51	0.71	0.04
CAP-072-114	OCEANIA GLASS 6ETClr	4.5	0.64	0.73	0.08
CAP-073-114	AGG IP Ctr 5/12Ar/5	2.8	0.51	0.70	0.27
CAP-114-01	5Clr/12Ar/5Clr/12Ar/5Clr	3.0	0.58	0.62	0.02
CAP-114-02	5ET/12Ar/5ClrET/12Ar/5Clr	2.4	0.48	0.53	0.02
CAP-114-11	AGG PRIME Ctr 6/12/6	3.1	0.48	0.59	0.02
CAP-114-12	AGG PRIME Ctr 8/12/8	3.0	0.47	0.58	0.02
CAP-114-21	AGG PLUS Ctr 6/12/6	2.9	0.52	0.68	0.02
CAP-114-22	AGG PLUS Ctr 8/12/8	2.8	0.51	0.67	0.02
CAP-114-29	AGG MAX Ctr 6/12/6	2.8	0.25	0.56	0.02
CAP-114-30	AGG MAX LI 6/12/6	2.8	0.25	0.57	0.02
CAP-114-35	6SolTGy/12Ar/10.5VLam-Hush	3.0	0.27	0.23	0.02

View full list of Residential and Commercial WERS rating at capral.com.au