



  
artisan™

ARCHITECTURAL  
992 AWNING & CASEMENT  
WINDOW

**CAPRAL**  
ALUMINIUM



## ARTISAN ARCHITECTURAL 992 AWNING & CASEMENT WINDOW

Whether opening from the top or the side, the Artisan Architectural 992 Awning & Casement Window is configurable to meet your needs. Smooth operation, a clean 100mm or 150mm outer frame, and custom hardware options make this a premium package.

This modern window is fully compatible and visually cohesive with the other windows in our Artisan Architectural range, ensuring a clean look and a premium feel.

### FEATURES AND BENEFITS

- Accepts double glazing up to 26mm alongside standard single glazing options
- Custom designed hardware options
- Awning configurations incorporate an integrated hook hinge at the head for strength
- Optional Caprice side latches to ensure security and performance on large sashes
- Integrated insect and security screening options for a modern, tidy aesthetic
- AGS 419, 429, 619, and 629 Flushline compatible for seamless integration
- Compatible with the full range of Artisan Architectural window suites



Capral's Artisan range is extruded in Australia using LocAl® Green primary aluminium.

- Significantly lower carbon emissions than global averages for primary aluminium
- 8kg CO<sub>2</sub>e/kg Al\*
- ASI Certified Smelter



\* Capral utilises a Mass Balance System in line with ISO 20095:2020 Chain of Custody to manage its LocAl Products. CO<sub>2</sub>e emissions stated are ex smelter based on kilograms emitted per kilogram of aluminium produced - Aluminium Smelting and Casting, International Aluminum Institute (IAI)



1800 ALUMINIUM (258 646)  
capral.com.au  
Capral Limited ABN 78 004 213 692  
March 2025

### MAXIMUM PERFORMANCE

Serviceability Pressure	3000Pa
Ultimate Pressure	4500Pa
Water Penetration	900Pa

### FRAME DIMENSIONS

Depth	100mm / 150mm
-------	---------------

### MAXIMUM RECOMMENDED SIZE

Height	2700mm
Width	2700mm
Max Area	3.24m <sup>2</sup> *
Weight	106kg

### GLAZING CAPACITY

Single Glazed	4-8mm
Thick Glazed	8-14mm
Double Glazed	12-26mm

### WINDOW ENERGY RATINGS

Window ID	Glazing	Uw	SHGC	Tw	Air Inf
CAP-551-01	10.38Clrlam	6.7	0.46	0.47	0.08
CAP-551-02	10ET	5.7	0.41	0.44	0.08
CAP-551-03	10.38ComPlsClr	5.7	0.41	0.44	0.08
CAP-551-07	6.38Clrlam	6.8	0.48	0.48	0.08
CAP-551-08	6Clr	6.8	0.51	0.49	0.08
CAP-551-09	6ET	5.8	0.44	0.45	0.08
CAP-551-10	5Clr	6.9	0.51	0.49	0.08
CAP-552-01	6.38Clr-12-6Clr	5.0	0.41	0.42	0.08
CAP-552-02	6.38Clr-12Ar-6Cl	4.9	0.41	0.42	0.08
CAP-552-03	6Clr-12-6Clr	5.0	0.43	0.42	0.08
CAP-552-04	6ET-12Ar-6Clr	4.5	0.38	0.39	0.08
CAP-552-05	4Clr-10-4Clr	5.1	0.46	0.44	0.08

\* Relies on the use of a twin chain winder

View full list of Residential and Commercial WERS rating at [capral.com.au](http://capral.com.au)