



artisan™

ARCHITECTURAL

994 SLIDING DOOR  
TOP HUNG

CAPRAL  
ALUMINIUM



## ARTISAN ARCHITECTURAL 994 TOP HUNG SLIDING DOOR

The Artisan Architectural 994 Top Hung Sliding Door is designed to succeed in both residential and commercial development projects. It is available as a one, two, three or four track door in recessed, corner, and cavity configurations.

The Artisan Architectural 994 Top Hung Sliding Door's top rolling hardware enhances its smooth operation. The system is compatible with Caprice and Caprio mortice and surface-mounted hardware.

### FEATURES AND BENEFITS

- Suited to almost any commercial or architectural application
- Top rolling capability improves operating force
- Single, double, triple and quad track configurations available
- Fully compatible with Aquago linear grate solution
- Flat thresholds and track infills provide a flat sill option
- Infill thresholds and linear grate covers which allow timber or tile inserts
- Low profile non-water-rated sill can be used for internal applications
- Corner and cavity configurations are available
- Top rolling hardware is easily adjusted and concealed with pelmet beads
- Compatible with Caprio and Caprice mortice and surface-mounted hardware



Capral's Artisan range is extruded in Australia using LocAl® Green primary aluminium.

- Significantly lower carbon emissions than global averages for primary aluminium
- 8kg CO<sub>2</sub>e/kg Al\*
- ASI Certified Smelter



\* Capral utilises a Mass Balance System in line with ISO 20095:2020 Chain of Custody to manage its LocAl Products. CO<sub>2</sub>e emissions stated are ex smelter based on kilograms emitted per kilogram of aluminium produced - Aluminium Smelting and Casting, International Aluminum Institute (IAI)



1800 ALUMINIUM (258 646)  
capral.com.au  
Capral Limited ABN 78 004 213 692  
January 2025

### MAXIMUM PERFORMANCE

Serviceability Pressure	1500Pa
Ultimate Pressure	3000Pa
Water Penetration	300Pa

### FRAME DIMENSIONS

Depth	100mm/150mm
Height	44mm/50mm/80mm

### MAXIMUM RECOMMENDED SIZE

Panel Height	3000mm
Panel Width	2500mm
Panel Weight	250kg

### GLAZING CAPACITY

Single Glazed	4-10mm
Thick Glazed	10-15mm
Double Glazed	19-26mm

### ACOUSTIC RATING

Acoustic (Max)	40 (-1;-4)
----------------	------------

### WINDOW ENERGY RATINGS

Window ID	Glazing	Uw	SHGC	Tw	Air Inf
CAP-056-01	6Clr	6.3	0.63	0.66	0.37
CAP-056-02	6Gy	6.3	0.45	0.33	0.37
CAP-056-23	10.38CPClr	4.6	0.50	0.60	0.37
CAP-056-24	10.38CPGy	4.6	0.38	0.29	0.37
CAP-057-01	6Clr/12/6Clr	3.9	0.55	0.59	0.37
CAP-057-03	6SpGy/12/6Clr	3.9	0.18	0.06	0.37
CAP-057-09	6Clr/12Ar/6Clr	3.8	0.55	0.59	0.37
CAP-057-10	6EG/12Ar/6Clr	3.8	0.31	0.35	0.37

View full list of Residential and Commercial WERS rating at [capral.com.au](http://capral.com.au)