




artisan™
ARCHITECTURAL
FOLDING SERVERY
WINDOW

CAPRAL
ALUMINIUM



ARTISAN ARCHITECTURAL FOLDING SERVERY WINDOW

The Artisan Architectural Folding Sery Window is a premium bi-fold option with a simple and smooth top-rolling action for easy access and simple operation. It's available in either single or double-glazed configurations with durable stainless steel hardware.

The sill-less design is perfect for use as a servery window, allowing clear views and convenient access. Open it fully to maximise airflow and access for entertaining or have just one panel open to let in a cool breeze – it's your choice!

FEATURES AND BENEFITS

- Single and double glazed options (up to 31mm)
- Top rolling system for smooth operation
- Sill-less design suits servery window
- Fully adjustable, including both horizontal and vertical
- Accepts double glazing providing excellent energy efficiency
- Complementary hardware from the Caprice range
- Euro spigot connectors save factory fabrication time
- Incorporates Stainless Steel hinges, rollers and flush-bolts
- Available in open in and open out configurations

MAXIMUM PERFORMANCE

| | |
|-------------------------|--------|
| Serviceability Pressure | 2400Pa |
| Ultimate Pressure | 5600Pa |
| Water Penetration | N/A |

FRAME DIMENSIONS

| | |
|-------|---------|
| Depth | 101.6mm |
|-------|---------|

MAXIMUM RECOMMENDED SIZE

| | |
|-------------|--------|
| Sash Height | 2100mm |
| Sash Width | 900mm |
| Sash Weight | 80kg |

GLAZING CAPACITY

| | |
|---------------|---------|
| Single Glazed | 4-12mm |
| Thick Glazed | 14-18mm |
| Double Glazed | 19-31mm |

WINDOW ENERGY RATINGS

| Window ID | Glazing | Uw | SHGC | T _w |
|-----------|-------------------|-----|------|----------------|
| CAP-557 | 5Clr | 6.3 | 0.50 | 0.50 |
| CAP-557 | 6ET | 5.1 | 0.42 | 0.46 |
| CAP-557 | 6Clr | 6.3 | 0.50 | 0.50 |
| CAP-557 | 6.38ClrLam | 6.2 | 0.47 | 0.50 |
| CAP-557 | 6.38CPClr | 5.1 | 0.42 | 0.46 |
| CAP-557 | 10.38CPClr | 5.0 | 0.39 | 0.45 |
| CAP-557 | 10ET | 5.0 | 0.40 | 0.45 |
| CAP-557 | 10.38ClrLam | 6.1 | 0.45 | 0.49 |
| CAP-558 | 4Clr/10Ar/4Clr | 4.5 | 0.47 | 0.46 |
| CAP-558 | 4Clr/10/4Clr | 4.6 | 0.47 | 0.46 |
| CAP-558 | 6ET/12Ar/6Clr | 4.0 | 0.38 | 0.41 |
| CAP-558 | 6Clr/12/6Clr | 4.5 | 0.43 | 0.44 |
| CAP-558 | 6.38Clr/12Ar/6Clr | 4.4 | 0.41 | 0.44 |
| CAP-558 | 6.38Clr/12/6Clr | 4.5 | 0.41 | 0.44 |



Capral's Artisan Architectural range is extruded in Australia using LocAl® Green primary aluminium.

- 50% lower-carbon emissions than global averages for primary aluminium
- 8kg CO₂e/kg Al
- ASI Certified Smelter



1800 ALUMINIUM (258 646)
capral.com.au
Capral Limited ABN 78 004 213 692
October 2022

View full list of Residential and Commercial WERS rating at capral.com.au