



artisan™

ARCHITECTURAL
FOLDING DOOR
VOLUME 2

CAPRAL
ALUMINIUM



ARTISAN ARCHITECTURAL FOLDING DOOR VOLUME 2

The Artisan Architectural Folding Door Volume 2 has smooth top rolling panels and allows for convenient use of floor space - open wide for uninhibited access when entertaining and close for protection from the elements. An ideal choice when you are looking to create flexible living areas.

Artisan Architectural Folding Doors suit a wide range of hardware and are configurable with sill and sill-less options to suit your climate and lifestyle.

FEATURES AND BENEFITS

- Top rolling hardware for ease of operation
- Water rated and non-water rated sills
- Compatible with the Aquago Linear Grate Sill
- Quick fit stainless steel hardware
- Multiple rail and midrail heights available
- Euro and commercial corner cleat assembly methods
- Large range of open-in and open-out configurations
- Fast Fix Hinge screw on hardware for ease of install
- Dedicated lock and cover stiles suit a large variety of hardware including Capral's Caprice and Caprio range



Capral's Artisan Architectural range is extruded in Australia using LocAl® Green primary aluminium.

- 50% lower-carbon emissions than global averages for primary aluminium
- 8kg CO₂e/kg Al
- ASI Certified Smelter



1800 ALUMINIUM (258 646)
capral.com.au
Capral Limited ABN 78 004 213 692
November 2022

MAXIMUM PERFORMANCE

Serviceability Pressure	3000Pa
Ultimate Pressure	5300Pa
Water Penetration - Static	450Pa

FRAME DIMENSIONS

Depth	101.6mm
-------	---------

MAXIMUM RECOMMENDED SIZE

Panel Height	2700mm*
Panel Width	900mm
Panel Weight	80kg

GLAZING CAPACITY

Single Glazed	4-12mm
Thick Glazed	14-18mm
Double Glazed	19-31mm

WINDOW ENERGY RATINGS

Window ID	Glazing	Uw	SHGC	Tw	Air Inf
CAP-562-01	6Clr/12/6Clr	4.1	0.49	0.52	0.13
CAP-562-02	6Clr/12Ar/6Clr	4	0.49	0.52	0.13
CAP-562-03	6Gy/12/6Clr	4.1	0.32	0.24	0.13
CAP-562-04	6EnTech/12Ar/6Clr	3.4	0.43	0.48	0.13
CAP-562-05	LightBridgeClrSO 6/12/6	3.3	0.4	0.51	0.13
CAP-562-06	LightBridgeGrySO 6/12/6	3.3	0.24	0.24	0.13
CAP-563-01	8Clr	5.9	0.53	0.56	0.12
CAP-563-02	638CPlsGy	4.6	0.34	0.25	0.08
CAP-563-03	638CPlsNtl	4.6	0.35	0.38	0.08
CAP-563-04	638CPlsClr	4.6	0.47	0.53	0.08
CAP-563-05	638ClrLam	5.9	0.53	0.57	0.12
CAP-563-06	6Clr	6	0.56	0.57	0.12

* With adjustable jamb hinge

View full list of Residential and Commercial WERS rating at capral.com.au