



  
artisan™  
ARCHITECTURAL  
TILT & TURN WINDOW

**CAPRAL**  
ALUMINIUM



## ARTISAN ARCHITECTURAL TILT & TURN WINDOW

The Artisan Architectural Tilt & Turn is a multi-functional window and is compatible with the AGS Flushline range of commercial framing products. The tilt option opens the window inwards at the top, allowing it to be left open for ventilation whilst being safe from children climbing out and intruders entering. Once the key is inserted, a turn of the handle opens the window from the side, giving you the ability to direct airflow, clean windows safely from the inside and providing a quick escape in case of emergencies.

The Artisan Architectural Tilt & Turn Window is an ideal solution to common problems in residential and commercial applications such as multi-storey apartments and hotel complexes. The multi-point locking system also provides excellent structural and water performance making it suitable for use in high wind cyclonic areas.

### FEATURES AND BENEFITS

- Single and double glazed options (up to 26mm)
- Standard and high performance configurations using sub frame system
- European designed components and hardware
- Multiple and adjustable locking points ensure structural integrity of the product is maintained even in high wind cyclonic areas
- Operable with a single handle with turn function restricted using a key override
- Inward opening allows for ease of cleaning
- An optional plant on screening adaptor
- Cyclonic debris impact resistance up to 15m/s



Capral's Artisan Architectural range is extruded in Australia using LocAl® Green primary aluminium.

- 50% lower-carbon emissions than global averages for primary aluminium
- 8kg CO<sub>2</sub>e/kg Al
- ASI Certified Smelter



1800 ALUMINIUM (258 646)  
capral.com.au  
Capral Limited ABN 78 004 213 692  
October 2022

### MAXIMUM PERFORMANCE

Serviceability Pressure	3000Pa
Ultimate Pressure	8000Pa
Water Penetration - Static	700Pa

### FRAME DIMENSIONS

Depth	100mm
-------	-------

### MAXIMUM RECOMMENDED SIZE

Sash Height	2100mm
Sash Width	1300mm
Sash Weight	80kg

### GLAZING CAPACITY

Single Glazed	4-12mm
Thick Glazed	14-18mm
Double Glazed	23-26mm

### ACOUSTICS

Acoustics	38(-1; -3)
-----------	------------

### WINDOW ENERGY RATINGS

Window ID	Glazing	Uw	SHGC	Tw	Air Inf
CAP-118-01	4Clr	6.7	0.43	0.39	0.12
CAP-118-02	6SpGy	6.7	0.21	0.04	0.12
CAP-118-03	6TS2IAz	6.4	0.18	0.07	0.12
CAP-118-04	6.38CPNtl	5.9	0.28	0.26	0.12
CAP-119-01	5Clr/10Ar/5Clr	5.3	0.37	0.35	0.12
CAP-119-02	6ET/12/6Clr	5.0	0.32	0.32	0.12
CAP-119-03	6ET/12Ar/6Clr	4.9	0.32	0.32	0.12
CAP-119-04	10.76LamClr/12/4Clr	5.3	0.33	0.34	0.12
CAP-119-05	LB Clr5/12/5	4.8	0.31	0.34	0.12
CAP-119-06	LB Gy5/12/5	4.8	0.21	0.18	0.12

View full list of Residential and Commercial WERS rating at [capral.com.au](http://capral.com.au)