



  
urban™  
RESIDENTIAL  
LIGHT SLIDING DOOR

**CAPRAL**  
ALUMINIUM



## URBAN LIGHT SLIDING DOOR

The Urban Light Sliding Door is a high performing residential non-stacking sliding door system. Featuring a lighter 95mm framing system and with a range of strength options, it covers a wide range of design possibilities.

For enhanced thermal performance, optional double glazing is also available with high quality rollers delivering a smooth and easy operation via elegant surface mounted hardware. Available in standard two track configurations of two, three and four panel non-stacking options.

Being part of the Capral Urban residential range, the Urban Sliding Door can be paired with a complementary selection of sliding, casement, awning and double hung windows to provide a total window and door solution.

### FEATURES AND BENEFITS

- Single and double glazing options
- Self draining sill design
- Various performance options
- Integrated insect and security screening options
- Standard lock options
- Compatible with Urban products
- Acoustic results available



Capral's Urban range is extruded in Australia using LocAl® Green primary aluminium.

- 50% lower-carbon emissions than global averages for primary aluminium
- 8kg CO<sub>2</sub>e/kg Al
- ASI Certified Smelter



1800 ALUMINIUM (258 646)  
 capral.com.au  
 Capral Limited ABN 78 004 213 692  
 October 2022

### MAXIMUM PERFORMANCE

Serviceability Pressure	2750Pa
Ultimate Pressure	4400Pa
Water Penetration	300Pa

### FRAME DIMENSIONS

	Depth	Height
Low Profile Sill	115mm	20mm
Standard Sill	95mm	32mm
Slotted Sill	95mm	48mm

### MAXIMUM RECOMMENDED SIZE

Height	2700mm
Width	1200mmSTD 1500mm HD
Weight	160kg

### GLAZING CAPACITY

Single Glazed	4mm-10mm
Double Glazed	10mm-18mm

### WINDOW ENERGY RATINGS

Window ID	Glazing	Uw	SHGC	Tw	Air Inf
CAP-036-01	4Clr	6.3	0.71	0.74	0.28
CAP-036-03	6.38DLam	6.2	0.69	0.74	0.28
CAP-036-04	6AzTS21	5.5	0.24	0.13	0.28
CAP-036-05	5Gy	6.3	0.52	0.39	0.28
CAP-036-06	6Gy	6.3	0.49	0.35	0.28
CAP-036-08	6.38DLamGy	6.2	0.53	0.37	0.28
CAP-037-01	6Clr/6/6Clr	4.3	0.58	0.63	0.28
CAP-037-13	AGG PRIME Clr 4/10/4	3.3	0.46	0.55	0.28
CAP-037-14	AGG PRIME Clr 5/8/5	3.4	0.46	0.55	0.28
CAP-037-20	AGG PLUS Clr 4/10/4	3.1	0.50	0.65	0.28
CAP-037-21	AGG PLUS Clr 5/8/5	3.2	0.49	0.64	0.28
CAP-037-22	AGG PLUS Clr 6/8/4	3.2	0.49	0.64	0.28
CAP-037-23	AGG PLUS Gy 4/10/4	3.1	0.36	0.41	0.28
CAP-037-24	AGG PLUS Gy 6/8/4	3.2	0.31	0.32	0.28
CAP-037-27	AGG MAX Clr 6/8/4	3.2	0.24	0.52	0.28

View full list of Residential WERS ratings at [capral.com.au](http://capral.com.au)