



ags<sup>TM</sup>

COMMERCIAL  
TILT & TURN WINDOW

CAPRAL  
ALUMINIUM



## AGS TILT & TURN WINDOW

The AGS Tilt & Turn window is flexible in both form and function. It is compatible with our AGS Narrowline range of commercial framing products, making it a great solution-focused addition to residential and commercial projects such as apartment complexes and hotels.

With the turn of a handle, the AGS Tilt & Turn shows its capabilities. In tilt mode, the window opens inward from the top to provide a safe and secure source of ventilation. When the key is inserted and the handle is rotated, the window opens from the side for directed airflow, cleaning or a simple escape route when a dangerous situation arises.

### FEATURES AND BENEFITS

- Single and double glazed options (up to 26mm)
- Standard and high performance configurations using sub frame system
- European designed components and hardware
- Multiple and adjustable locking points ensure structural integrity of the product is maintained even in high wind cyclonic areas
- Turn function is restricted using a key override
- Optional plant on screening adaptor
- Inward opening allows for ease of cleaning
- Operable with a single handle
- Cyclonic debris impact resistance up to 15m/s



Capral's AGS range is extruded in Australia using LocAL<sup>®</sup> Green primary aluminium.

- 50% lower-carbon emissions than global averages for primary aluminium
- 8kg CO<sub>2</sub>e/kg Al
- ASI Certified Smelter



1800 ALUMINIUM (258 646)  
capral.com.au  
Capral Limited ABN 78 004 213 692  
October 2022

### MAXIMUM PERFORMANCE

Serviceability Pressure	4500Pa
Ultimate Pressure	4500Pa
Water Penetration - Static	600Pa

### FRAME DIMENSIONS

Depth	101.6mm
-------	---------

### MAXIMUM RECOMMENDED SIZE

Sash Height	2100mm
Sash Width	1300mm
Sash Weight	80kg

### GLAZING CAPACITY\*

Single Glazed	4-12mm
Thick Glazed	14-18mm
Double Glazed	23-26mm

### ACOUSTICS

Acoustics	38(-1; -3)
-----------	------------

### WINDOW ENERGY RATINGS

Window ID	Glazing	Uw	SHGC	Tw	Air Inf
CAP-120-01	4Clr	6.5	0.43	0.41	0.58
CAP-120-02	6SpGy	6.5	0.20	0.04	0.58
CAP-120-03	6TS21Az	6.1	0.17	0.07	0.58
CAP-120-04	6.38CPNtl	5.6	0.28	0.27	0.58
CAP-120-05	SOLOS 6.38 KSL Ntl	4.9	0.36	0.38	0.58
CAP-121-01	5Clr/10Ar/5Clr	5.0	0.37	0.36	0.58
CAP-121-02	6ET/12/6Clr	4.7	0.32	0.33	0.58
CAP-121-03	6ET/12Ar/6Clr	4.6	0.32	0.33	0.58
CAP-121-04	LB Clr5/12/5	4.6	0.30	0.36	0.58
CAP-121-05	LB Gy5/12/5	4.6	0.21	0.19	0.58

View full list of Residential and Commercial WERS rating at [capral.com.au](http://capral.com.au)

\* Listed glazing capacity only relates to Tilt & Turn products.