



agsTM

COMMERCIAL
50 COMMERCIAL
MULTI-POINT AWNING WINDOW

CAPRAL
ALUMINIUM



AGS 50 COMMERCIAL MULTI-POINT AWNING WINDOW

The AGS 50 Commercial Multi-Point Awning Window provides high-performance in a clean commercial frame. The panel's integrated multi-point locking provides significantly increased strength and security, ideal for use in high-rise buildings.

The system is compatible with both AGS Narrowline and Futureline framing systems to maximise compatibility and visual consistency across any project.

FEATURES AND BENEFITS

- Suits most commercial and architectural applications
- Compatible with a range of AGS 100mm and 150mm double glazed frames
- Continuous hook hinge or stay hinge method
- High degree of design flexibility
- Integrated multi-point locking hardware
- Range of locking points available



Capral's AGS range is extruded in Australia using LocAL® Green primary aluminium.

- Significantly lower carbon emissions than global averages for primary aluminium
- ASI Certified Smelter



Capral utilises a Mass Balance System in line with ISO 20095:2020 Chain of Custody to manage its LocAL Products. CO₂e emissions stated are ex smelter based on kilograms emitted per kilogram of aluminium produced - Aluminium Smelting and Casting, International Aluminum Institute (IAI)



1800 ALUMINIUM (258 646)
capral.com.au
Capral Limited ABN 78 004 213 692
December 2025

MAXIMUM PERFORMANCE

Serviceability (Pa)	2500
Ultimate (Pa)	4500
Water (Pa)	600

FRAME DIMENSIONS

429 Flushline Frame	100mm
629 Flushline Frame	150mm

MAXIMUM RECOMMENDED SIZE

Panel Height	2000mm
Panel Width	1300mm
Panel Area	2.5m ²
Weight	60kg

GLAZING CAPACITY

Double Glazed	24mm-40mm
---------------	-----------

WINDOW ENERGY RATINGS

Window ID	Glazing	Uw	SHGC	T _w	Air Inf
50 MULTI-POINT AWNING INTO 429 FLUSHLINE					
CAP-606-001	6CPGy/12Ar/6Clr	4.8	0.24	0.15	0.10
CAP-606-002	6CPClr/12Ar/6Clr	4.9	0.32	0.32	0.10
CAP-606-003	6Clr/12/6Clr	5.3	0.37	0.34	0.10
CAP-606-004	6Clr/12Ar/6Clr	5.2	0.37	0.34	0.10
CAP-606-005	6ET/12Ar/6Clr	4.9	0.32	0.32	0.10
CAP-606-006	AGG PLUS Clr 6/12/6	4.8	0.30	0.34	0.10
50 AWNING INTO 425 NARROWLINE					
CAP-607-001	6CPGy/12Ar/6Clr	5.2	0.24	0.15	0.10
CAP-607-002	6CPClr/12Ar/6Clr	5.2	0.32	0.32	0.10
CAP-607-003	6Clr/12/6Clr	5.6	0.37	0.34	0.10
CAP-607-004	6Clr/12Ar/6Clr	5.5	0.37	0.34	0.10
CAP-607-005	6ET/12Ar/6Clr	5.2	0.33	0.32	0.10
CAP-607-006	AGG PLUS Clr 6/12/6	5.1	0.31	0.34	0.10

View full list of Residential and Commercial WERs rating at capral.com.au